


HERZ-Two-Port-Flanged Valve

F 4035 XX


Datasheet „2-Port Valves, flanged“ PN 16 and PN 25

☑ Dimensions in mm (PN16)



Order Nr. PN 16	DN	Stroke [mm]	kvs	D	L	Number of flange bores	d	d _k	h ₁	H	kg
F 4035 16	50	20	40	165	230	4		125	90	305	12,5
F 4035 07	65	20	63	185	290			145	135	315	20
F 4035 08	80	20	100	200	310	8		160	150	350	26
F 4035 09	100	40	160	220	350			180	160	480	38
F 4035 10	125	40	250	250	400			210	185	520	64
F 4035 41	150	40	330	285	480		23	240	180	525	77

☑ Dimensions in mm (PN25)



Order Nr. PN 25	DN	Stroke [mm]	kvs	D	L	Number of flange bores	d	d _k	h ₁	H	kg
F 4035 40	15	10	1	95	130	4	14	65	68	250	4,5
F 4035 51	15	10	1,6	95	130			65	68	250	4,5
F 4035 61	15	10	2,5	95	130			65	68	250	4,5
F 4035 71	15	14	4	95	130			65	68	250	4,5
F 4035 43	25	20	6,3	115	160			85	85	255	7,5
F 4035 53	25	20	10	115	160			85	85	255	7,5
F 4035 44	32	20	16	140	180	8	19	100	105	305	10,5
F 4035 45	40	20	25	150	200			110	115	315	11
F 4035 56	50	20	40	165	230			125	125	320	12,5
F 4035 47	65	40	63	185	290			145	132	465	25
F 4035 48	80	40	100	200	310			160	105	510	34
F 4035 49	100	40	160	235	350			190	127	540	49
F 4035 50	125	40	250	270	400		28	220	170	505	65
F 4035 52	150	40	330	300	480			250	180	545	84

PN16					Leakage acc. to 12266-1
Order number	DN	Differential pressure max. [bar]			Direct flow branch
F 4035 16	50		3		≤0.01%kvs
F 4035 07	65		1,5		
F 4035 08	80		1,5		
F 4035 09	100			2	
F 4035 10	125			1	
F 4035 41	150			1	

PN25					Leakage acc. to 12266-1
Order number	DN	Differential pressure max. [bar]			Direct flow branch
F 4035 40	15	4			≤0.1%kvs
F 4035 51	15	4			
F 4035 61	15	4			
F 4035 71	15	4			
F 4035 43	25	4			
F 4035 53	25	4			
F 4035 44	32		4		
F 4035 45	40		4		
F 4035 56	50		3		
F 4035 47	65			2.5	
F 4035 48	80			2.5	
F 4035 49	100			2	
F 4035 50	125			1	
F 4035 52	150			1	

☑ Technical data and material

Max. operating pressure	16 bar (PN16), 25 bar (PN25)
Min. operating temperature	5 °C
Max. operating temperature	150 °C
Valve curve characteristic	equal percentage
Type of connection	Flanges (EN 1092-2)
Valve body material for PN16	EN-GJL-250 (EN 1561)
Valve body material for PN25	EN-GJS-400-18-LT (EN 1563)
Sealing element material	70EPDM
Valve seat material	WN1.4021
Valve cone material (PN16)	WN1.4021/brass
Valve cone material (PN25)	
up to DN 50	WN1.4021
from DN 65 to DN 150	EN-GJL-250/WN1.4021
Stem material	WN1.4404

Water purity in accordance with the ÖNORM H 5195 and VDI 2035 standards.

☑ Description


The two port flanged valve is primarily designed to control the flow of circulation water in district heating and HVAC systems, as well as for remote closing of heating pipelines. Circulation medium should be cold, warm and hot water in temperature range from 5°C to 150°C. The valve can be utilized in almost all heating, ventilation and air-conditioning systems and in industrial and technological processes. The valve curve is equal percentage. Regulation ratio (ratio between nominal and minimal flow coefficient) is 30:1. The selection of the two port flanged valve is according to the diagram of kvs values.

For PN16: Valve is closed when the stem is out. Valve is open when the stem is depressed.


For PN25, DN15-65 and DN125-150: Valve is closed when the stem is out. Valve is open when the stem is depressed.

For PN25, DN80-100: Valve is open when the stem is out. Valve is closed when the stem is depressed.


☑ Selection diagram



Application examples



Valve in injection circuit



Valve in throttle circuit

Installation

The valve can be installed in all positions, from horizontal to vertical, except in vertical position with the actuator pointing downwards. The arrow on the valve body must match the direction of fluid flow through the valve. The valves must be installed for the correct application using clean fittings. A HERZ strainer (4111) should be fitted to prevent impurities during operation. Therefore an installation is recommended.

For installation, the local and international standards have to be followed.

